



70-2000-0006



series: BEAM Workplace luminaires

Type of installation: portable
 Type of Protection: **IP 65**
 Protection Class: II
 Lamp/Wattage: 1 x LED 43 W 5000 K

Housing plastic (polycarbonate, edge guard made of soft thermoplastic elastomer TPE), cover plastic opal (polycarbonate), retractable stainless steel mounting hook with safeguard, second cable entry optional (through-wiring option), 3 m power supply cable with mains plug

electro-technics:

Electric Gear Converter
 System Capacity 47 W
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Power supply cable H07RN-F
 Size power supply cable 2 x 1,0 mm²
 Length power supply cable 3 m
 Colour power supply cable black
 Connector systems E+F, Konturenst. (CEE 7/17)

testings:

Type of Protection **IP 65**
 Protection Class II
 Safety Marks D-mark, F-mark
 Other Marks WEEE mark
 Country Code CE
 Energy efficiency class LED A++
 Energy efficiency class of included lamp A++

lamp 1:

Colour Temperature 5000 K
 Lamp LED
 Number of Lamps 1
 Wattage 43,00 W

weights and measures:

Length L 352 mm
 Width B 223 mm
 Height H 357 mm
 Weight 1,838 kg

lighting technology:

Colour Rendering Index (CRI) 80
 Luminaire flux 4.500 lm