



68A40106-0062



series: Schutzrohrleuchten LED Tube lights

Type of installation: universal mounting system
 Type of Protection: **IP 44**
 Protection Class: I
 Lamp/Wattage: 4 x LED 10 W 5000 K
 Colour: grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 protectors blue, socket, power supply cable with mains plug, incl. LED panel

electro-technics:

Electric Gear Converter
 System Capacity 45 W
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour TPE blue
 Power supply cable H07RN-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Socket outlets 1
 Connector systems CEE-12h
 Lamp cover opal

testings:

Type of Protection **IP 44**
 Safety Marks F-mark
 Energy efficiency class of included lamp A++
 Protection Class I
 Glow Wire Test 650°C - 30 seconds
 Impact Protection IK08 (5 Joule)
 Other Marks WEEE mark
 Energy efficiency class LED A++

lamp 1:

Socket without socket
 Colour Temperature 5000 K
 Lamp LED
 Number of Lamps 4
 Wattage 10,00 W

weights and measures:

Diameter D 120 mm
 Length L 1.310 mm
 Weight 3,4 kg

lighting technology:

Luminaire flux 5.300 lm

accessories

68Z00001 grey
 68Z00002 silver coloured
 68Z00003
 68Z00004
 68Z00005
 68Z00006