



83-012B0-0006



series: GLADIATOR SL I Workplace luminaires

Type of installation: portable
 Type of Protection: **IP 44**
 Protection Class: I
 Lamp/Wattage: 1 x LED 36 W 5000 K
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), two sockets and switch, power supply cable with mains plug

electro-technics:

Electric Gear Converter
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour TPE blue
 Colour handle black
 Power supply cable H07RN-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Additional functions with switch
 Connector systems Typ E (CEE 7/5)
 Socket outlets 2
 Lamp cover opal

testings:

Type of Protection **IP 44**
 Protection Class I
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code CE
 Energy efficiency class LED A++
 Energy efficiency class of included lamp A++

lamp 1:

Socket without socket
 Colour Temperature 5000 K
 Lamp LED
 Number of Lamps 1
 Wattage 36,00 W

weights and measures:

Length L 283 mm
 Width B 272 mm
 Height H 104 mm
 Weight 2,71 kg

lighting technology:

Colour Rendering Index (CRI) 80
 Luminaire flux 4.000 lm

accessories

95-0170-0001 Tripod Standard, without castors, set with mounting rail for 1 work light
 95-0171-0001 Tripod Standard, with castors, set with mounting rail for 1 work light
 95-0172-0001 Tripod Standard, without castors, set with mounting rail for 2 work lights
 95-0173-0001 Tripod Standard, with castors, set with mounting rail for 2 work lights
 95-0270-0001 Magnet set, for attachment to the threaded bushes in the handle black
 95-0268-0001 Mounting rail for one GLADIATOR SL I or SL II black
 95-0269-0001 Mounting rail for 2x GLADIATOR SL I or SL II black
 95-0061-0001 Tripod 'Profi', 3-part, extendable up to 3.20 m blank
 95-0290-0006 Transport bag for work light blue