



# 88-0L000-0006



series: GLADIATOR II LED Workplace luminaires

Type of installation:portableType of Protection:IP 66Protection Class:IILamp/Wattage:1 x LED 28 W 5000 KColour:black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), power supply cable with mains plug, incl. LED panel

#### accessories

|   | Mounting rail for 1 or 2 work lights anthracite metallic 1Mounting rail for 1 work light, for tripod and wall |  |
|---|---|--|
|   | mounting  |  |
| 95-0003-0001  | Tripod 'Standard', without castors  |  |
| 95-0004-0001  | Tripod 'Standard', with castors   |  |
| 95-0005-0001  | Tripod 'Standard', without castors, set with mounting rail for 2 work lights                                  |  |
| 95-0006-0001  | Tripod 'Standard', with castors, set with mounting rail for 2 work lights                                     |  |
| 95-0007-0022  | Magnetic holder, for attachment 1 or 2 work lights anthracite metallic  |  |
| 95-0008-0001  | Tripod 'Standard', without castors, set with mounting rail for 1 work light                                   |  |
| 95-0009-0001  | Tripod 'Standard', with castors, set with mounting rail for 1 work light                                      |  |
| 95-0013-0022.2 Magnetic holder, for attachment 1 work light |   |  |
| 95-0017-0022  | Spigot 30 mm, conforming to DIN 14640 anthracite  |  |
| 95-0021-0014  | Fixing device for scaffolding, with mounting rail for 1 work light  |  |
| 95-0026-0022  | Female spigot 30 mm, for attachment of a mounting rail anthracite   |  |
| 95-0061-0001  | Tripod 'Profi', 3-part, extendable up to 3.20 m blank   |  |
| 95-0290-0006  | Transport bag for work light blue   |  |

## electro-technics:

Electric Gear System Capacity Voltage Converter 32 W 220 - 240 V / 50 - 60 Hz

E+F, Konturenst. (CEE 7/17)

650°C - 30 seconds IK08 (5 Joule)

blue

5 m

black

opal

IP 66

D-mark

CE

A++

A++

WEEE mark

Ш

black

H07RN-F

2 x 1,0 mm<sup>2</sup>

#### Spezifikationen:

Colour TPE Colour handle Power supply cable Size power supply cable Length power supply cable Colour power supply cable Connector systems Lamp cover

#### testings:

Type of Protection Protection Class Glow Wire Test Impact Protection Safety Marks Other Marks Country Code Energy efficiency class LED Energy efficiency class of included lamp

#### lamp 1:

# Socketwithout socketColour Temperature5000 KLampLEDNumber of Lamps1Wattage28,00 W

## weights and measures:

| Length L | 320 mm   |
|----------|----------|
| Width B  | 305 mm   |
| Height H | 110 mm   |
| Weight   | 2,228 kg |

# lighting technology:

| Colour Rendering Index (CRI) | 80       |
|------------------------------|----------|
| Luminaire flux               | 3.400 lm |

SONLUX Lighting GmbH • Frankenhäuser Str. 66 • D-99706 Sondershausen Tel. +49 3632 6522-0 • info@sonlux.de • www.sonlux.de