



# 88-0N000-0006



series: GLADIATOR II LED Workplace luminaires

Type of installation: portable  
 Type of Protection: **IP 65**  
 Protection Class: II  
 Lamp/Wattage: 1 x LED 28 W 5000 K  
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), switch, emergency light function, power supply cable with mains plug, incl. LED panel

## electro-technics:

Electric Gear Converter  
 System Capacity 32 W  
 Voltage 220 - 240 V / 50 - 60 Hz

## Spezifikationen:

Colour TPE blue  
 Colour handle black  
 Power supply cable H07RN-F  
 Size power supply cable 2 x 1,0 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Additional functions with switch, with 'TNF'  
 Connector systems E+F, Konturenst. (CEE 7/17)  
 Lamp cover opal

## testings:

Type of Protection **IP 65**  
 Protection Class II  
 Glow Wire Test 650°C - 30 seconds  
 Impact Protection IK08 (5 Joule)  
 Safety Marks D-mark  
 Other Marks WEEE mark  
 Country Code CE  
 Energy efficiency class LED A++  
 Energy efficiency class of included lamp A++

## lamp 1:

Socket without socket  
 Colour Temperature 5000 K  
 Lamp LED  
 Number of Lamps 1  
 Wattage 28,00 W

## weights and measures:

Length L 320 mm  
 Width B 305 mm  
 Height H 110 mm  
 Weight 2,7 kg

## lighting technology:

Colour Rendering Index (CRI) 80  
 Luminaire flux 3.400 lm

## accessories

90-0004-0022 Mounting rail for 1 or 2 work lights anthracite metallic  
 90-0005-0022 Mounting rail for 1 work light, for tripod and wall mounting  
 95-0003-0001 Tripod 'Standard', without castors  
 95-0004-0001 Tripod 'Standard', with castors  
 95-0005-0001 Tripod 'Standard', without castors, set with mounting rail for 2 work lights  
 95-0006-0001 Tripod 'Standard', with castors, set with mounting rail for 2 work lights  
 95-0007-0022 Magnetic holder, for attachment 1 or 2 work lights anthracite metallic  
 95-0008-0001 Tripod 'Standard', without castors, set with mounting rail for 1 work light  
 95-0009-0001 Tripod 'Standard', with castors, set with mounting rail for 1 work light  
 95-0013-0022 Magnetic holder, for attachment 1 work light  
 95-0017-0022 Spigot 30 mm, conforming to DIN 14640 anthracite  
 95-0021-0014 Fixing device for scaffolding, with mounting rail for 1 work light  
 95-0026-0022 Female spigot 30 mm, for attachment of a mounting rail anthracite  
 95-0061-0001 Tripod 'Profi', 3-part, extendable up to 3.20 m blank  
 95-0290-0006 Transport bag for work light blue