



# 68A10100-0062

series: Schutzrohrleuchten LED Tube lights

Type of installation: universal mounting system  
 Type of Protection: **IP 54**  
 Protection Class: I  
 Lamp/Wattage: 1 x LED 10 W 5000 K  
 Colour: grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 protectors blue, socket, power supply cable with mains plug, incl. LED panel

### electro-technics:

Electric Gear Converter  
 System Capacity 12 W  
 Voltage 220 - 240 V / 0 Hz, 50 - 60 Hz

### Spezifikationen:

Colour TPE blue  
 Power supply cable H07RN-F  
 Size power supply cable 3 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Socket outlets 1  
 Lamp cover opal  
 Connector systems Typ F, Schuko (CEE 7/4)

### testings:

Type of Protection **IP 54**  
 Glow Wire Test 650°C - 30 seconds  
 Impact Protection IK08 (5 Joule)  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Protection Class I  
 Energy efficiency class LED A++  
 Energy efficiency class of included lamp A++

### lamp 1:

Socket without socket  
 Colour Temperature 5000 K  
 Lamp LED  
 Number of Lamps 1  
 Wattage 10,00 W

### weights and measures:

Diameter D 120 mm  
 Length L 470 mm  
 Weight 1,926 kg

### lighting technology:

Luminaire flux 1.200 lm  
 Colour Rendering Index (CRI) 80

### accessories

68Z00001 grey  
 68Z00002 silver coloured  
 68Z00003  
 68Z00004  
 68Z00005  
 68Z00006