



80C01000-0006



series: POWERCASE modular and linear luminaires

Type of installation: portable
 Type of Protection: IP 66
 Protection Class: I
 Lamp: LED
 Colour: blue

Gehäuse Aluminium / Kunststoff, Abdeckung klares Polycarbonat mit Linsenoptik, abnehmbare Zuleitung mit Netzstecker und Potentiometer (stufenlos dimmbar 10-100%), inkl. Adapter für DIN-Zapfen-Aufnahme (d=30 mm, DIN 14640) mit der Möglichkeit einer geraden oder 30° geneigten Montage

electro-technics:

Electric Gear Converter, dimmable, 1-10V
 System Capacity 630 W
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Power supply cable H07BQ-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 10 m
 Colour power supply cable yellow
 Additional functions with switch
 Connector systems Typ E+F, Schuko (CEE 7/7)
 Lamp cover clear

testings:

Type of Protection IP 66
 Protection Class I
 Impact Protection IK08 (5 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code CE
 Energy efficiency class LED A++
 Energy efficiency class of included lamp A++

lamp 1:

Lamp LED
 Number of Lamps 8
 Wattage 71,50 W
 Socket without socket
 Colour Temperature 5000 K
 Colour rendering index (CRI) 80
 Lifespan

weights and measures:

Length L 884 mm
 Width B 225 mm
 Height H 495 mm
 Weight 19 kg

lighting technology:

Luminaire flux 83.500 lm

accessories

- 95-0060-0014 **Crank tripod Premium**, incl. Tripod adapter 28 mm / 30 mm (DIN 14640) chrome, smooth finish
- 95-0060-0014 **Crank tripod Premium**, incl. Tripod adapter 28 mm / 30 mm (DIN 14640), bracing set and carrier box chrome, smooth finish
- 95-0254-0014 **Tripod adapter**, 28 mm / 30 mm (DIN 14640) stainless steel
- 95-0265-0040 **Carrier box for Tripod "Premium"**, wood, 2 carrier handles
- 95-0266-0001 Rubberized joint feet for Crank tripod 'Premium' (Set 3x) stainless steel
- 95-0267-0001 Bracing set, 3x rope cord and peg