



POWERCASE L

LARGE AREA LIGHTING

POWERCASE L

Portable lighting for large areas



POWERCASE L - the next generation

POWERCASE L, the upgraded large-area luminaire in a unique suitcase design, now provides even more light with the same multifunctionality. During rescue and emergency operations or when securing the scene of a crime, on construction and civil engineering sites or at public events: proper lighting is a must, an absolute requirement and a success factor. POWERCASE L delivers this light in impeccable daylight quality with a spectacular luminous flux of 100,000 lumens.

ADDITIONAL ADVANTAGES

- ⊕ Unique case design with handle for convenient and quick transportation
- ⊕ Multifunctional use: standing on the ground, suspended or mounted to tripod
- ⊕ Maintenance-free (passive cooling)
- ⊕ Suitable for wind loads up to 150 km/h
- ⊕ Robust, impact-resistant construction
- ⊕ Dimmable
- ⊕ Versions with Casambi Bluetooth® control for wireless networking available
- ⊕ Functional upgrades by changing the power cable (dimmable, Casambi, etc.)
- ⊕ Environmentally friendly and conserves resources thanks to replaceable components



IP 65

IK08



POSSIBLE APPLICATIONS

- + Building trade
- + Industry
- + Emergency and rescue services
(technical relief services, police, fire service,
Red Cross, etc.)
- + Event management

POWERCASE L

Features




Unique case design and immediate ready-to-use



High degree of protection IP 65

How passive cooling works
In our passively cooled lighting fixtures, the heat inside the fixture is dissipated via an aluminium element, thus obviating the need for active cooling and rendering the lighting fixtures maintenancefree.



Environmentally friendly and conserves resources thanks to replaceable components



Versions with Casambi Bluetooth® control for wireless networking available




Impact-resistant and break-proof housing




Integrated carry handle



Low heat generation, no cooling phase so immediately portable



Dimmable versions available



Power cable can be removed/swapped
Alternative plug systems and power cable lengths on request




Protective cover for safe transportation

POWERCASE L




Aluminium / plastic housing, clear polycarbonate cover with lens optics, detachable power supply cable with mains plug and potentiometer, infinitely adjustable, incl. adapter for spigot (DIN 14640 certified) with the possibility of straight or 30° angled assembly, incl. transport cover.



L 949, B 884, H 137 mm



- Φ_v 100.000 lm effective
- 5.000 K, $R_a \geq 80$
8 x LED panel
- 10 m, H07BQ-F
yellow
- IK08




L 884, B 225, H 495 mm

	P						
230 V, 50-60 Hz							
80C03000-0006	775 W	-	I	IP 65	E+F	20,4 kg	
80C03001-0006	775 W	-	I	IP 65	E+F ⁶⁸	20,4 kg	
80C03006-0006	775 W	-	I	IP 65	CEE 6h	20,4 kg	
80C030CH-0006	775 W	-	I	IP 65	J	20,4 kg	
80C04000-0006	775 W	0 ... 100 %	I	IP 65	E+F	20,4 kg	
80C04001-0006	775 W	0 ... 100 %	I	IP 65	E+F ⁶⁸	20,4 kg	
80C04006-0006	775 W	0 ... 100 %	I	IP 65	CEE 6h	20,4 kg	
80C040CH-0006	775 W	0 ... 100 %	I	IP 65	J	20,4 kg	
80C05000-0006	775 W	2 x (0 ... 100 %)*	I	IP 65	E+F	20,4 kg	
80C05001-0006	775 W	2 x (0 ... 100 %)*	I	IP 65	E+F ⁶⁸	20,4 kg	
80C05006-0006	775 W	2 x (0 ... 100 %)*	I	IP 65	CEE 6h	20,4 kg	
80C050CH-0006	775 W	2 x (0 ... 100 %)*	I	IP 65	J	20,4 kg	

*separately dimmable





Aluminium / plastic housing, clear polycarbonate cover with lens optics, detachable power supply cable with mains plug and potentiometer, infinitely adjustable, incl. adapter for spigot (DIN 14640 certified) with the possibility of straight or 30° angled assembly, incl. transport cover.




L 949, B 884, H 137 mm

	P						
230 V, 50-60 Hz							
80C04000-0006.B	775 W	2 x (0 ... 100 %)*	I	IP 65	E+F	20,4 kg	
80C04001-0006.B	775 W	2 x (0 ... 100 %)*	I	IP 65	E+F ⁶⁸	20,4 kg	
80C04006-0006.B	775 W	2 x (0 ... 100 %)*	I	IP 65	CEE 6h	20,4 kg	
80C040CH-0006.B	775 W	2 x (0 ... 100 %)*	I	IP 65	J	20,4 kg	

*separately dimmable



- Φ_v 100.000 lm effective
- 5.000 K, $R_a \geq 80$
8 x LED panel
- 10 m, H07BQ-F
yellow
- IK08




L 884, B 225, H 495 mm


Smart Control


Smart Control stands for the intelligent remote control of our luminaires via mobile app from a mobile phone or tablet. It doesn't matter whether individual luminaires or groups of luminaires are to be controlled. All luminaires - even existing ones - can be controlled together with an integrated „Casambi“ module. Thus also our POWERTUBE II, POWERDISK and POWERCASE L. The luminaires are networked via Bluetooth from the mobile device to the luminaire and from luminaire to luminaire, which considerably increases the range of the luminaire network.

- ON/OFF
- Dimming
- Timer
- Scenes
- Animations



Specifications subject to alteration.





Crank tripod “Premium“

Steel, chrome plated, suitable for 16 & 28 mm spigots, safety bolt, self braking clutch / winch, fold-away crank, one adjustable stand to compensate uneven terrain

incl. tripod adapter 28 mm/30 mm (DIN 14640)

Packed dimensions:
L 1.850, B 230, H 160 mm

	95-0060-0014.D		Hmax 3800, Hmin 1740, D 1300 mm		22,5 kg
--	----------------	--	---------------------------------	--	---------



Crank tripod „LightmaXX“

Galvanised steel, chrome-plated and powder-coated, with spigot adapter, automatic safety lock, 1 foot adjustable for levelling on uneven ground, self-braking coupling, fold-away elevator

incl. tripod adapter 28 mm/30 mm (DIN 14640)

incl. clamping kit for tripod

Pack dimensions:
L 1.810, B 300, H 250 mm

	95-0294-0014		Hmax 4130, Hmin 1750, D 1730 mm		25,0 kg
--	--------------	--	---------------------------------	--	---------



Hinged feet with rubber pad

For crank tripod “Premium”, stainless steel, Set (3 pieces)



	95-0266-0001		0,43 kg
--	--------------	--	---------



Bracing set

3 x rope cord and peg

	95-0267-0001		1,1 kg
--	--------------	--	--------



Tripod adapter
28 mm/30 mm (DIN 14640)

Stainless steel, for connection to existing stands with 28 mm

	95-0254-0014		L 108, D 38 mm		0,5 kg
--	--------------	--	----------------	--	--------

Carrier box for
Tripod “Premium“

Wood, 2 carrier handles
(set with tripod: right side)

	95-0265-0040		L 1990, B 325, H 225 mm		21,2 kg
--	--------------	--	-------------------------	--	---------



Set
Crank tripod “Premium“

The set includes:

Crank tripod “Premium”, tripod adapter, bracing set, carrier box

	95-0060-0014S1	L 1990, B 325, H 225 mm		44,0 kg
--	----------------	-------------------------	--	---------



Set

2x belt strap incl. snap hook
For suspended mounting of POWERCASE L

	95-0227-0001	L 1000 mm		0,56 kg
--	--------------	-----------	--	---------





Mobiles Licht für Profis – Made in Germany

Portable light for professionals – Made in Germany

*Éclairage mobile pour les professionnels –
Fabriqué en Allemagne*

SONLUX Lighting GmbH

Frankenhäuser Straße 66
99706 Sondershausen
Germany

Phone +49 3632 6522 - 0
Fax +49 3632 6522 - 822

www.sonlux.de
info@sonlux.de



Tip with added value:

The digital version of this publication contains **interactive links** that lead you from the article number directly to the web.

