# POWERTUBE II M


### 73P01000-0006 |





Large-area lights 4017506119750 D 270, H 590

portable grey



Large area luminaire. Housing: aluminium, powder-coated. Base plate of steel, powder-coated, with rubber feet. Cover opal, made of impact-and break-resistant plastic (polycarbonate). Uniform, soft and glare-reduced illumination. Can be used on a tripod, as a floor lamp or suspended. Holding sleeve for stand spigot d=30mm, DIN 14640. Toggle switch (off, 180° illumination, 360° illumination). Incl. carrying bag.

**Product specifications** 

Product specifications	
Diameter D	270 mm
Height H	590 mm
Weight	9.58 kg
Supply cable / plug	5 m, H07RN-F, 2 x 1,0 mm <sup>2</sup> / Typ E+F (CEE 7/17)
additional functions	with switch
Light source	LED
Colour temperature	5000 K
Rated luminous flux	12000 lm   24000 lm
System power	94 W   187 W
System efficiency	128 lm/W   128 lm/W
Glare evaluation RUG (4H 8H)	28,1   29,8
Beam angle	down 180°   90°/90°/0°/90°
	up 180°   90°/90°/0°/90°
LED rated life	50000 h (L80/B50)
Colour rendering index (CRI)	80
Photobiological safety according to EN 62471	Risk group 0
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	3
Luminaires on B16A fuse	5
Luminaires on C10A fuse	5
Luminaires on C16A fuse	8
Inrush current / Inrush current duration	100 A / 209 μs
CIE Flux Code / CEN Flux Code	12 36 66 50 100
Type of protection	IP 65
Protection class	II
Filament test	850 °C
Impact resistance	IK08
Ambient temperature	-20 °C to + 30 °C
Safety marks	D-mark
Conformity mark	CE

## **POWERTUBE II M**

#### 73P01000-0006 |



#### **Accessories**



95-0060-0014.D Crank tripod 'Premium', Hmax 3,80 m, Hmin 1,74m



95-0265-0040 Carrier box for telescopic tripod 'Premium', wood, 2 carrier handles



95-0257-0014 Tripod 'Professional', Hmax 4,45m, Hmin 1,1m



95-0264-0001 Carrier box for telescopic tripod 'Professionell', black, 2 carrying belt, 1 shoulder belt



95-0257-0014S1 Set Tripod "Professionell", includes Tripod 'Professionell' and carrier box



95-0266-0001 Rubberized joint feet for Crank tripod 'Premium' (Set 3x)



95-0060-0014S1 Crank tripod 'Premium', incl. Tripod adapter d=30 mm (DIN 14640), bracing set and carrier box



95-0267-0001 Bracing set, 3x rope cord and peg



95-0258-0040 Transport box for telescopic tripod 'Professional'



95-0225-0001 Belt strap incl. snap hook

## POWERTUBE II M 73P01000-0006 |







